

# CHEM INTERNATIONAL

## **MATERIAL SAFETY DATA SHEET**

**EMERGENCY #: CANUTEC (613) 996-6666**

### PRODUCT IDENTIFICATION AND PREPARATION INFORMATION

**PRODUCT NAME:** CI Loose All

**EFFECTIVE DATE:** January 8, 2009

**WHMIS CLASS:** Class A; Class D - Div 2B

**T.D.G. CLASSIFICATION:** CONSUMER COMMODITY · ORM-D

**UN:**

**PG:**

**MATERIAL USE:**

### HAZARDOUS INGREDIENTS

CHEMICAL NAME	CAS #	%WT	TWA/TLV	LD 50	LC 50
Mineral Oil	8042-47-5	40-50	5mg/m3	N/D	N/D
Dipropylene Glycol Monomethyl Ether	34590-94-8	01-05	100 ppm	N/D	N/D
Octamethylcyclotetrasiloxane	556-67-2	01-05	10 ppm	N/D	N/D
Decamethylcyclopentasiloxane	541-02-6	01-05	10 ppm	N/D	N/D
Carbon Dioxide	124-38-9	01-05	10000 ppm	N/D	N/D

### PHYSICAL DATA

**BOILING POINT(°F):** ~ 260° C

**VAPOUR PRESSURE (psig @20°C):** 68

**SPECIFIC GRAVITY (H<sub>2</sub>O=1) @23° C:** 0.833

**VAPOUR DENSITY (Air=1):** >1

**SOLUBILITY IN WATER:** Slight

**Total VOC (Volatile Organic Compound) %:** 3%

**APPEARANCE AND ODOUR:** Brownish Liquid, Solvent Odor

### FIRE AND EXPLOSION DATA

**FLAMMABILITY:** (as per Flame Projection Test): Non-Flammable Spray

**FLASH POINT (Deg C method):** >93° C

**MEANS OF EXTINCTION:** Foam, CO 2, Dry Media

**SPECIAL FIRE FIGHTING PROCEDURES:** Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

**FIRE AND EXPLOSION HAZARDS:** Exposure to temperature above 49° C may cause bursting.

### REACTIVITY DATA

**STABILITY:** Material Stable.

**INCOMPATIBILITY:** Avoid contact with strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Dioxide, Carbon Monoxide.

**REACTIVITY:** Hazardous Polymerization Will not Occur.

### FIRST AID

**EYE:** Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

**SKIN:** Wash with soap and water. If irritation persists seek medical attention.

**INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

**INGESTION:** Do not induce vomiting. Seek medical attention immediately.

## TOXICOLOGICAL PROPERTIES

**ROUTE OF ENTRY:** Eyes contact ( ), Skin contact ( ), Skin absorption ( ), Inhalation ( ), Ingestion ( )

### EFFECTS OF ACUTE EXPOSURE:

**EYES:** May cause slight irritation but does not injure eye tissue.

**SKIN:** Frequent or prolonged contact may cause irritation.

**INHALATION:** Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.

**INGESTION:** Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis. Minimal toxicity.

### EFFECTS OF CHRONIC EXPOSURE:

**CARCINOGENICITY:** Non Hazardous by WHMIS Criteria

**REPRODUCTIVE TOXIN:** N/D

**TERATOGENICITY:** N/D

**MUTAGENICITY:** N/D

**SYNERGISTIC MATERIALS:** N/D

**EXPOSURE LIMITS:**

## PREVENTATIVE MEASURES

**GLOVES:** None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.

**EYE PROTECTION:** None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.

**RESPIRATORY PROTECTION:** None needed for proper use in accordance with label directions.

**ENGINEERING CONTROLS: Ventilation:** Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

**LEAK AND SPILL PROCEDURE:** Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, Provincial and local laws.

**WASTE DISPOSAL:** Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, Provincial and local authorities for approved procedures.

**STORAGE REQUIREMENTS:** Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 49° C.

**HANDLING PROCEDURES: KEEP OUT OF REACH OF CHILDREN.** For Industrial and Institutional use only.

N/AP= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · N/AV=NOT AVAILABLE  
<=LESS THAN - >=MORE THAN

## HMIS HAZARD RATING INFORMATION

FIRE	REACTIVITY	HEALTH	PERSONAL PROTECTION
1	0	1	B

0 – Minimal, 1- Slight, 2 – Moderate, 3 – Serious, 4 – Extreme.

DISCLAIMER: Information for this material safety data sheet was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases, data is not available and is so stated. Since conditions of actual product use are beyond the control of the supplier, it is assumed that the user of this material has been fully trained according to the mandatory requirements of WHIMIS. No warranty, expressed or implied is made, and supplier will not be liable for any losses, injuries, or consequential damage that may result from the use or reliance on any information contained in this form.

## CHEM INTERNATIONAL

18043 – 107 Avenue  
Edmonton, Alberta  
T5S 1K3  
1 (800) 665-7287