

TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY: Eyes, skin contact, inhalation, ingestion

EFFECTS OF ACUTE EXPOSURE:

EYES: "Frostbite like effects may occur if the liquid or escaping vapors contact the eyes.

SKIN: Immediate effects of overexposure may include: Frostbite if liquid or vapor contact is made with the skin.

INHALATION: Inhalation of high concentrations of vapor is harmful & may cause heart irregularities, unconsciousness, or death. Intentional misuse or deliberate inhalation may cause death without warning. Vapors are heavier than air and may accumulate in low lying or confined areas.

INGESTION: Ingestion is not considered a potential route of exposure.

EFFECTS OF CHRONIC EXPOSURE:

SKIN: Immediate effects of overexposure may include: Frostbite if liquid or vapor contact is made with the skin.

IRRITANCY: N/AV

RESPIRATORY TRACT SENSITIZATION: N/AV

CARCINOGENICITY: N/AV

REPRODUCTIVE TOXIN: N/AV

TERATOGENICITY: N/AV

MUTAGENICITY: N/AV

SYNERGISTIC MATERIALS: N/AV

EXPOSURE LIMITS:

PREVENTATIVE MEASURES

RESPIRATORY PROTECTION: None needed for proper use in accordance with label directions.

VENTILATION: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

PROTECTIVE GLOVES: None needed for proper use in accordance with label directions. Use impervious gloves if hand contact will be made.

EYE PROTECTION: None needed unless it is anticipated that a splash or spray back will occur, then wear safety glasses or chemical proof goggles.

OTHER PROTECTIVE EQUIPMENT: N/AV

ENGINEERING CONTROLS: N/AV

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, Provincial and local authorities for approved procedures.

KEEP OUT OF REACH OF CHILDREN.

For Industrial and Institutional use only.

Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120° F.

NFPA Code 30B Rating: Level 1 Aerosol.

N/AP= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · N/AV=NOT AVAILABLE
<=LESS THAN - >=MORE THAN

HMIS HAZARD RATING INFORMATION

FIRE	REACTIVITY	HEALTH	PERSONAL PROTECTION
0	0	1	B

0 – Minimal, 1- Slight, 2 – Moderate, 3 – Serious, 4 – Extreme.

DISCLAIMER: Information for this material safety data sheet was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases, data is not available and is so stated. Since conditions of actual product use are beyond the control of the supplier, it is assumed that the user of this material has been fully trained according to the mandatory requirements of WHIMIS. No warranty, expressed or implied is made, and supplier will not be liable for any losses, injuries, or consequential damage that may result from the use or reliance on any information contained in this form.

CHEM INTERNATIONAL

18043 – 107 Avenue
Edmonton, Alberta
T5S 1K3
1-800-665-7287